

UNCLASSIFIED

AD NUMBER
AD851310
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; 06 JUN 1960. Other requests shall be referred to Space and Missile Systems Organization, Los Angeles, CA.
AUTHORITY
SAMSO ltr, 20 Mar 1972

THIS PAGE IS UNCLASSIFIED

AD 851310

UNCLASSIFIED

SECRET

REPORT NO. ZN-7-366

DATE 6 June 1960

NO. OF PAGES 71

CONFIDENTIAL

Classification Changed To:
UNCLASSIFIED

Authorized By:
D D 254 MSCG

Reclassified By:
Richard J. Green

Date 5-14-60
WS1079
Dept. 1301

RANGE AND GUIDANCE ACCURACY CAPABILITY

OF THE

ATLAS MISSILE SYSTEM

CONVAIR-
ASTRONAUTICS

JUN 17 1960

LIBRARY

PREPARED BY H.W. Sorenson
H. W. Sorenson

APPROVED BY R. M. Leger
R. M. Leger

CHECKED BY J. L. Greenstein
J. L. Greenstein

APPROVED BY W. H. Schwidetzky
W. H. Schwidetzky

FLIGHT PERFORMANCE AND GUIDANCE ANALYSIS

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of:
Hq. SAMS, LA., Ca. 90045
Attn: SMSD

MAY 5 1959

DOWNGRADED AT 3 APR 1978
ALS. DECLASSIFIED AFTER 12 YEARS
DOD DIR 32000

CONFIDENTIAL

UNCLASSIFIED

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, USC, SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW

Best Available Copy

SECRET

SECRET

ZN-7-386

FOREWORD

An estimate of the accuracy of the two guidance systems used by the Atlas missile system is presented in this report. An approximate indication of the size of the payload that can be delivered to ranges from 4700 n. miles to 8700 n. miles is also given.

SECRET

SECRET

ZN-7-366

TABLE OF CONTENTS

<u>Item</u>	<u>Page</u>
FOREWORD	1
TABLE OF CONTENTS	11
LIST OF TABLES	111
LIST OF FIGURES	iv
SUMMARY.	1
INTRODUCTION	4
DISCUSSION	5
RESULTS.	10
LIST OF REFERENCES	13

SECRET

~~SECRET~~

2N-7-366

LIST OF TABLES

<u>Table</u>		<u>Page</u>
I	C.E.P. FOR RADIO-INERTIAL GUIDANCE SYSTEM.	14
II	C.E.P. FOR ALL-INERTIAL GUIDANCE SYSTEM.	15
III	TOTAL R.S.S. MISS FOR 1 σ ERRORS IN RIG SYSTEM	16
IV	SUMMARY OF RADIO-INERTIAL ERROR STUDY.	
	Section 1	17
	Section 2	19
	Section 3	21
	Section 4	23
V	TOTAL R.S.S. MISS FOR 1 σ ERRORS IN AIG SYSTEM	25
VI	SUMMARY OF INERTIAL ERROR STUDY.	
	Section 1	26
	Section 2	30
	Section 3	34
	Section 4	38

~~SECRET~~

~~CONFIDENTIAL~~
SECRET

ZN-7-366

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	a) Payload Versus Range for Various Tilt Rates.	42
	b) Payload Versus Tilt Rate for Various Ranges.	43
2	a) Payload Versus Range for Various Inertial Attitudes.	44
	b) Payload Versus Attitude for Various Ranges	45
3	C.E.P. for RIG System.	46
4	C.E.P. for AIG System.	47
5	Total Downrange Miss for RIG System.	48
6	Total Crossrange Miss for RIG System	49
7	RIG System Downrange Miss for Individual Error Sources .	
	a) For range of 4750 n. miles	50
	b) For range of 5500 n. miles	51
	c) For range of 6900 n. miles	52
	d) For range of 8700 n. miles	53
8	RIG System Crossrange Miss for Individual Error Sources.	
	a) For range of 4750 n. miles	54
	b) For range of 5500 n. miles	55
	c) For range of 6900 n. miles	56
	d) For range of 8700 n. miles	57
9	Total Downrange Miss for AIG System.	58
10	Total Crossrange Miss for AIG System	59

SECRET

SECRET

ZN-7-366

Figure

Page

11	AIG System Downrange Miss for Individual Error Sources .	
	a) For range of 4750 n. miles	60
	b) For range of 5500 n. miles	61
	c) For range of 6900 n. miles	62
	d) For range of 8700 n. miles	63
12	AIG System Crossrange Miss for Individual Error Sources.	
	a) For range of 4750 n. miles	64
	b) For range of 5500 n. miles	65
	c) For range of 6900 n. miles	66
	d) For range of 8700 n. miles	67
13	Relationship Between Power Cutoff Flight Path Angle And:	
	a) Sustainer stage tilt rate.	68
	b) Sustainer stage inertial attitude.	69
14	Circular Error Probability From Elliptical Probability Distribution	70
15	Downrange Miss Due to Q Tracking Error	71

SECRET

~~SECRET~~

~~CONFIDENTIAL~~

Page 1

SUMMARY

This report has attempted to answer two questions; first, the range to which various size payloads can be sent and second, the accuracy to which these payloads can be delivered by the guidance systems now available.

A typical D series missile configuration was selected for the purposes of this study. A nominal launch weight of 265,190 lbs. was used and the Rocketdyne MA-2 engines were assumed to produce nominal thrust and specific impulse. The missile that was simulated was launched due north from Vandenberg AFB. The accuracies of two different guidance systems, the G.E. Mod. III radio-inertial and the ARMA Lot IV all-inertial, have been studied and the results included in the text of this report.

Four burnout weights were used to establish the ranges at which the guidance system accuracies were determined. These trajectories were flown with a constant missile inertial attitude of 23.4° during sustainer stage. The following table summarizes these results.

Burnout Weight	Payload	Range (Approx.)	C.E.P.	
			G. E. Mod III System	ARMA System
lbs	lbs	n. miles	n. miles	n. miles
13,642	6000	4750	.61	1.08
12,642	5000	5500	.44	1.25
11,142	3500	6900	1.05	1.57
9,642	2000	8700	2.63	1.97

~~SECRET~~

~~SECRET~~

~~CONFIDENTIAL~~

ZN-7-366

Page 2

It was found that the C.E.P.'s could be made smaller by pitching the missile during sustainer stage. The payloads associated with the minimum error trajectories were changed to allow the same range to be reached. These results are listed in the following table. It is obvious from the table that the decrease in error results in lower payload capability.

Range (Approx.)	Payload, lbs		C.E.P., n. miles	
	G.E. Mod III	ARMA	G.E. Mod III	ARMA
4750	5325	5700	.34	1.03
5500	4850	4550	.43	1.20
6900	3600	3000	1.03	1.51
8700	1150	1500	2.23	1.86

It was also found that the maximum payload that can be sent to the 6900 and 8700 n. mile ranges were 3800 and 3000 lbs. As shown in the following table, this is at the expense of an increase in the C.E.P.. The location of the rate antenna would have to be changed if the G.E. System were used. The look angle requirements are not satisfied in the maximum payload trajectories.

Range (Approx.)	Payload	C.E.P., n. miles	
		G.E. Mod III	ARMA
n. miles	lbs		
6900	3800	0.85	2.55
8700	3000	3.87	3.70

~~SECRET~~

SECRET

~~CONFIDENTIAL~~

ZN-7-366
Page 3

The values of the C.E.P.'s given in this report will be optimistic due to omission of various sources of impact dispersions for which the guidance system cannot predict or correct. The dispersions caused by the effects of geophysical, atmospheric re-entry, and cutoff uncertainties will be of the order of 0.5 n. miles; so the cases which indicate a guidance system C.E.P. of this magnitude will be affected significantly.

SECRET

~~CONFIDENTIAL~~

SECRET

CONFIDENTIAL

ZN-7-366
Page 4

INTRODUCTION

This report deals with the range capability of the D series missile for various payloads and the guidance accuracies of both the radio-inertial (RIG) and all-inertial (AIG) guidance systems. The ranges considered were 4750 n. miles, 5500 n. miles, 6900 n. miles, and 8700 n. miles. Although the range capability may change for later series missiles due to changes or design improvements, (i.e., such as the change to MA-3 engines), the guidance error partials at the ranges considered in this study should not be affected greatly.

All of the cases presented herein use the same missile configuration; the only variables are the sustainer and vernier burnout weights and the second stage tilt program. The data for the report was obtained by using a missile trajectory simulation, as described in detail in Reference 1, and radio-inertial and inertial guidance error programs.

Two different guidance systems have been considered, the General Electric Mod. III radio-inertial and the ARMA all-inertial systems. Errors in these systems lead to target misses, the size of the miss being dependent upon the magnitude of the error, the trajectory, and the distance to the target. The errors used to obtain the misses are the 1 σ values as quoted by G.E. and ARMA. The target errors can be minimized by pitching during sustainer stage, as is shown later in the report. Target misses also result from sources other than the guidance system but these errors have not been considered in this report (e.g., re-entry winds, geophysical uncertainties, vernier cutoff errors, and atmospheric density variations).

SECRET

CONFIDENTIAL

SECRET

ZN-7-366
Page 5

DISCUSSION

Basic Trajectory Information

The trajectories simulated for this report are those of a nominal D series missile launched due north from Vandenberg AFB. Every trajectory was based on a missile launch weight of 265,190 lbs., a booster jettison weight of 7,197 lbs., nominal thrust and specific impulse (i.e., booster and sustainer engines specific impulses were 251 seconds and 219.3 seconds), and a staging time of 135 seconds. In addition, the D series tilt program was attenuated by a factor of 0.97. The tracker simulated for the radio-inertial guidance (hereafter referred to as RIG) portion of the error study was for the G.E. Mod. III guidance system with the "q" baseline oriented directly downrange and the "p" crossrange.

Four trajectories were flown to establish the ranges at which the error studies were made. These four trajectories were simulated with a constant missile inertial attitude of 23.4° during sustainer stage. The only differences between the trajectories were the sustainer burnout weights, which were taken to be 13,642 lbs., 12,642 lbs., 11,142 lbs., and 9,642 lbs. These burnout weights apply to a D-R&D vehicle and correspond approximately to payloads of 6000 lbs., 5000 lbs., 3500 lbs., and 2000 lbs., respectively. A D-IOC missile is capable of carrying about 1100 lbs. more payload for comparable sustainer burnout weights.

An oblate (Clarke's spheroid of 1866), rotating earth model was assumed in the simulation. The ICAO standard atmosphere was used during both powered flight and nose cone re-entry. To conserve computer time, a spherical earth and vacuum re-entry were assumed in finding the error partials. These approximations will cause little change in the partials since the errors are relative quantities.

Varying Attitude Trajectories

In addition to the four constant attitude cases, trajectories were simulated which included pitch rates during sustainer stage. This was done in an effort to minimize the target miss due to errors in the guidance systems. Trajectories that were flown to minimize the misses for the RIG system had a constant tilt rate throughout sustainer stage. Runs for the all-inertial guidance (hereafter referred to as AIG) system had a rapid tilt at the start of sustainer stage with a constant attitude thereafter. A rapid tilt rate was used in order to simulate the ARMA system. The missile is pitched in accordance with the function:

$$\omega_\eta = 0.2 (\epsilon - \epsilon_0)$$

The tilt rate in deg./sec. is denoted by ω_η ; ϵ is the missile attitude (i.e., angle between missile roll axis and launch horizontal) at the initiation of guidance; and ϵ_0 is the desired missile attitude. ϵ and ϵ_0 have the units of degrees in this equation.

SECRET

SECRET

ZN-7-366

Page 6

Powered flight for all of these runs was terminated when the missile had attained the velocity necessary to hit the previously established impact point. This enabled the error study to be made at the same four ranges. The tilt rates in sustainer stage will cause the size of the payload that can be delivered to a given range to be different than that for the constant attitude case. The amount of change is discussed in the results.

The RIG System Errors

The RIG System can be considered to be composed of two subsystems, one ground-based and the other airborne. Included in the ground-based equipment is a tracker which measures the position and velocity of the missile in terms of six quantities: slant range (R), elevation angle (γ), azimuth angle (A), slant range rate ($\dot{R}$), and two lateral rate quantities ($\dot{P}$ and $\dot{Q}$). For this study, the system error is considered to be due solely to bias errors in the tracking quantities. The tracker bias errors used in this report were obtained from Reference 3 and are listed in Table IV. They were the latest available 10 values for the G.E. Mod. III System when the computations of the target miss presented herein were made.* These errors were assumed to be the same for the various trajectories simulated. The slant range error given in the table is in kilofeet rather than feet. This was done to prevent the values of the partials from becoming too unwieldy.

The RIG System imposes a constraint on the trajectory that is not present for vehicles that are flown with no guidance or with the AIG System. The tracker must receive good rate data during the latter part of sustainer stage if sustainer shutdown is to occur at the proper instant. To insure that good data are being obtained, the radar cone angle θ_L (i.e., the angle between the line of sight from the tracker to the missile and the longitudinal axis of the vehicle) must be greater than 2° for the last 30 seconds of sustainer stage. In addition, the tracking antenna must view the top of the missile during this period since the rate antenna is located on the top.

Because of the look angle constraint, the missile cannot be pitched down at too fast a rate if lock is to be maintained. For the configuration in this study the maximum rate was approximately $+0.02^\circ/\text{sec}$. The data pertaining to the larger rates would be applicable if the antenna were moved to a location on the bottom of the missile.

The AIG System Errors

The AIG System is composed of an airborne computer and an inertially stabilized platform upon which three accelerometers are placed. The accelerometers are

* The latest G.E. estimates of the tracking errors are given in Reference 5 and indicate the R.M.S. of the bias and residual noise errors to be of the same order of magnitude as the bias errors used in this report.

SECRET

SECRET

ZN-7-366

Page 7

mounted so as to form an orthogonal coordinate system, the axes being designated by x, y, and z. The platform and accelerometers are oriented prior to launch by ground-based alignment equipment. The x-axis is oriented downrange toward the target and the y-axis is directed in a crossrange direction. The z-axis is aligned along the plumb bob vertical to form a right-handed system. The accelerometers are used to sense the thrust and aerodynamic accelerations in the three orthogonal directions. The measured accelerations are fed to the airborne computer which computes the gravity accelerations, sums the measured and computed accelerations, and then integrates to obtain position and velocity. The position and velocity are used to determine the time of sustainer and vernier cutoff and to generate the yaw steering signals.

According to Reference 4, there are five general sources of error in the AIG system; the gyros, accelerometers, platform, computer, and ground support equipment. In this study, none of the sources of error in the computer were considered but their omission should not affect the system C.E.P. to any sizable degree. It can be seen in Reference 4 that the computer errors are the least significant of any of the five.

Most of the major contributors to the error in the remaining four parts of the system have been considered. Since all effects could not be considered, the results of the study will give an optimistic value of accuracy and should not be expected to give the best possible estimate for the entire system. It does indicate the manner in which the major errors change with sustainer attitude and with trajectory range and is valuable in this respect.

There are a number of causes of error in each of the above sources that are considered. The following paragraphs give a brief description of the causes. For a more complete discussion, see Reference 4.

If the gyros which align the platform drift for any reason, the orientation of the platform and accelerometers will be changed and errors will result in the measurement of acceleration. There are, in general, three types of drifts that could occur: constant drifts, drifts that are proportional to the acceleration, and drifts that are proportional to the square of acceleration. A fixed drift of $0.1^\circ/\text{hr}$. (which represents the drift remaining after compensation) was assumed for each gyro.

The spin axis of the pitch gyro lies in the plane of the x and z platform axes and was offset from the x axis by 54° in this study. The offset minimizes the downrange errors resulting from the behavior of the thrust acceleration. On Page 16 of Reference 4 there is a brief discussion of the offset and the error involved in the offset.

A mass unbalance drift of $.36^\circ/\text{hr/g}$ due to an unbalance along the outer wire axis of the pitch gyro was considered for the pitch gyro mass unbalance error. If the compromise offset angle for the trajectories were optimum, little or no miss would result from this unbalance so the error is actually a combination of the two effects. The mass unbalance error for the roll-azimuth gyro was attributed to an unbalance along the spin axis of the ball. The characteristics of two, single degree of freedom gyros, one for roll and the other for yaw, were used to obtain the partials and the results are given in that form. When these results are applied to the two degree of freedom gyro used in the ARMA system,

SECRET

SECRET

ZN-7-366

Page 8

only one change has to be made. The crossrange errors for the two gyros is such that the roll gyro error partially cancels that of the yaw gyro. In the results this effect has been taken into account and the errors have been combined. The effect of a gimbal mass unbalance along the spin axis of the gyro has also been studied. It was assumed to have an effect equivalent to that for a roll gyro spin axis mass unbalance drift. No temperature sensitive mass unbalance drifts have been included.

An error of $0.15^\circ/\text{hr/g}$ was used in calculating the miss distance due to the mass unbalance along the spin axis of the roll-azimuth gyro. This value represents two errors listed in Reference 4. The value given in the gyro data in Reference 4 (Table 3) has been combined with the roll-azimuth gyro drift compensation uncertainty that is quoted among other ground support equipment errors in Table 10 of that report. A figure of $0.15^\circ/\text{hr/g}$ has also been used for the gimbal mass unbalance and corresponds to the value given in Table 3. Note that all values used in the target miss computations are based on the ARMA Lot IV system.

Accelerometer errors consist of a bias or zero error, a g sensitive or scale factor error, and g^2 and g^3 sensitive errors. The value of uncertainty in the setting of the accelerometer zero that was used is the R.S.S. sum of three terms; the linearity, the measurement uncertainty, and the x and z offset resolutions. The latter two are included in the GSE section (Table 10) of Reference 4.

Two errors have been combined to give the value used for the scale factor effect, the uncertainty due to linearity and the measurement uncertainty (a GSE error). Inclusion of the latter is not entirely correct since the miss partial for it should be slightly different. With present capability no differentiation could be made between the two; so, rather than omit it completely, it has been added in this manner.

The values used for the K_2 and K_3 effects are the same as given in Reference 4 for the K_2 acceleration and the K_3 uncertainty errors.

Accelerometer misalignment errors are the only platform errors considered. Two types of misalignments are possible; a perfectly aligned pair of accelerometers (i.e., exactly at right angles to each other) may not be perfectly aligned with the pendulum, or a pair of axes may not be orthogonal to one another. The non orthogonal alignments considered are the z-axis in pitch, the y-axis in azimuth and roll, and the x-axis in pitch. The x-axis could be misaligned in azimuth and the z-axis in roll but this would only result in a cosine effect and is negligible.

Misalignments of a pair of axes in pitch, yaw, and roll have been studied. Values of errors in this section are the R.S.S. values of similar errors in both Tables 7 and 10 of Reference 4. No servo errors were included in the study.

It has been mentioned in preceding paragraphs that the system accuracy quoted in the results will be somewhat optimistic due to omission of certain errors. The C.E.P. quoted in Reference 4 for the Lot IV system was 1.46 n. miles. When calculated using the values given in that report for all the effects that have been considered for this study, the C.E.P. was found to be 1.21 n. miles. This comparison gives some indication of the amount the results of this study could be in error.

SECRET

SECRET

ZN-7-366

Page 9

Guidance Error Programs

Two digital computer programs, which were developed specifically to simulate the errors that can appear in the two types of guidance systems, were used to find the error partials. The program used to obtain the RIG errors alters the position or velocity vector at vernier cutoff in such a manner as to duplicate the amount by which the particular tracker quantity under study is supposed to be in error. The impact point obtained using the altered vector is then compared with the reference impact location to obtain the target miss and error partial.

The AIG error program uses as input the powered flight time history of acceleration and inertial attitude of the missile as obtained from the reference trajectory, and alters these quantities in the way the various error sources would be expected to affect them. The altered position and velocity at vernier cutoff are then used to obtain an impact location, which, when compared with the reference impact, yields the target miss and error partial.

SECRET

~~CONFIDENTIAL~~
SECRET

ZN-7-366
Page 10

RESULTS

Range and Payload Capabilities

The maximum range of a missile carrying a payload of 6000 lbs., 5000 lbs., 3500 lbs., or 2000 lbs. was found to be 4766 n. miles, 5478 n. miles, 6889 n. miles, or 8724 n. miles respectively for missile trajectories in which a constant missile inertial attitude of 23.4° was maintained during sustainer stage. The RIG and AIG error studies were made at these ranges although, for the sake of brevity, the ranges are referred to as 4750 n. miles, 5500 n. miles, 6900 n. miles, and 8700 n. miles.

In Figure 1(a) the payload of the missile is plotted against range for various sustainer stage tilt rates. The role of range and tilt rate is reversed in Figure 1(b). The negative tilt rates that are shown refer to a pitch up maneuver, whereas the positive tilt rates indicate a pitch down. Similar plots of payload, range, and missile inertial attitude can be found in Figure 2(a) and 2(b). It can be seen from these plots that the lower trajectories increase the payload capability at the longer ranges.

RIG Error Study

A summary of the C.E.P.'s obtained for each of the trajectories in the RIG portion of the study can be found in Table I. A plot of these data is given in Figure 3. The C.E.P.'s were computed in the manner described in Reference 4. A plot from the reference has been reproduced and is included as Figure 14.

Reference to Figures 5 and 6, which are plots of downrange and crossrange miss, shows that the shape of the C.E.P. curves is due primarily to the behavior of the downrange misses. The dominant effect in the downrange miss is the Q tracking error, as can be seen by looking at Table IV or Figure 7, and is directly responsible for the manner in which the system C.E.P. and downrange miss behaves at the different ranges.

Table IV and Figures 7 and 8 contain the values of downrange and crossrange miss that result from the assumed tracking errors for each of the ranges included in the study. The numbers in the tables and graphs represent the absolute value of the miss. The downrange miss due to the Q errors can be seen to reach a sharp minimum at the two shorter ranges. This minimum represents the point where the miss becomes zero and indicates a change in sign of the miss.

Tracking errors in Q are reflected as errors in the flight path angle γ and missile velocity V_m . For some trajectories the misses due to changes in these two quantities are additive, for others they are subtractive. This is the reason the misses go through zero and the slope of the plots varies from range to range. Figure 15 has been included to give a pictorial idea of the manner in which the miss due to Q errors varies with range and tilt rate.

SECRET

SECRET

ZN-7-366
Page 11

Tracking errors in P are the major source of crossrange miss at the 4750 n. mile and 5500 n. mile ranges. At the two longer ranges the Q errors become very important contributors to this miss. The crossrange miss due to Q errors can be attributed to earth rotation effects. The situation has been exaggerated somewhat due to the fact the trajectory impact locations vary from 65° N latitude for the 4750 n. mile case to 3° S latitude for the 8700 n. mile case.

AIG Error Study

The C.E.P.'s obtained for each of the trajectories in the AIG portion of the study are summarized in Table II and plotted in Figure 4. It is interesting to note that the case with an inertial attitude of 23.4° and range of 5500 n. miles (i.e., the case that corresponds most closely to the one in Reference 4) yields a C.E.P. of 1.25 n. miles. It was pointed out in the discussion earlier in this report that a C.E.P. of 1.21 n. miles was obtained from the ARMA data when only the errors included in this study were considered. The results indicate the system C.E.P. to be relatively insensitive to the inertial attitude in the region from $\epsilon = 20^\circ$ to $\epsilon = 30^\circ$. The optimum attitude for missiles using the AIG system would appear to be dependent on the payload or range capability of the missile for the various attitudes in this range of magnitude.

Table V lists the total R.S.S. value of downrange and crossrange miss for the AIG trajectories. These values have been plotted and are included as Figures 9 and 10. The graphs show the results to be consistent except for the crossrange miss for the 8700 n. mile case. The increase in the miss at the low attitude angles for this case can be seen to be due to errors in the accelerometer. Section 4(b) of Table VI or Figure 12(d) verifies this. As was true with the Q error in the RIG portion of the study, the increase is the result of earth rotation effects.

Figures 11 and 12 are plots of target miss against missile inertial attitude for each error source and each range. It can be seen that the largest source of downrange error can be attributed to the accelerometers. Gyro errors yield the smallest misses at 4750 and 5500 n. miles but become a more important contributor with increasing range.

The system target miss was found to increase as the trajectories became lower. Therefore, the size of the payload that can be delivered to a target, particularly those at ranges of over 6000 n. miles, will be limited by the guidance accuracy that is required.

The results obtained from examination of a number of errors have been omitted from this report. This was done because the miss from these errors was insignificant and could be neglected. Such items as gyro anisclastic effects, y-accelerometer scale factor, g^2 , and g^3 effects, and x and z accelerometer misalignment in roll are examples of errors that have been omitted.

Among the figures found in the latter part of the report are plots relating tilt rate and inertial attitude to the flight path angle at power cutoff. These plots are denoted as Figures 13(a) and 13(b).

SECRET

SECRET

ZN-7-366

Page 12

Comparison of RIG and AIG Systems

The constant attitude trajectories that were used for the RIG error study correspond exactly to the AIG trajectories in which a missile attitude of 23.4° was maintained. Comparison of the C.E.P.'s for these cases shows that the RIG system gives the smallest values, except at the extreme range of 8700 n. miles. The following table gives a concise summary of these results.

Range	C.E.P.	
	RIG System	AIG System
4750	.61	1.08
5500	.44	1.25
6900	1.05	1.57
8700	2.63	1.97

When the RIG system errors were minimized, it was found that little improvement could be obtained for the 4750 and 5500 n. mile cases. A tilt rate of $+1^\circ/\text{sec.}$ was found to decrease the error at 6900 n. miles to .89 n. miles, an improvement of .16 n. miles. Unfortunately, the look angle requirements were not met for any trajectory that was pitched at a rate greater than $.02^\circ/\text{sec.}$; so the location of the radar antenna would have to be changed from the top to the bottom of the missile if this trajectory were to be flown. The C.E.P. can be reduced to 1.03 n. miles by pitching the missile at the rate of $+0.02^\circ/\text{sec.}$, but this represents a negligible improvement. The smallest error that can be achieved at the 8700 n. mile range is heavily dependent upon the size of the payload that could be flown. If a 1100 lb. payload were available for use with the Atlas, the error could be reduced to 2.23 n. miles by pitching at $-0.05^\circ/\text{sec.}$ The lightest nose cone now being used weighs approximately 2100 lbs.

The AIG system errors could not be improved very much at the shorter ranges either. They could be decreased slightly at the longer ranges by flying at an attitude of $\epsilon_0 \approx 28^\circ$. This would result in a loss of 500 lbs. in the payload that could be delivered to a target 8700 n. miles from the launch site and would only improve the guidance accuracy by .1 n. mile. By decreasing the accuracy to that obtained for the constant attitude trajectory in the RIG study, the payload could be increased to approximately 2375 lbs. from 2000 lbs.

SECRET

SECRET

ZN-7-366
Page 13

LIST OF REFERENCES

1. Munroe/Sorenson "IBM 704 Flight Performance Simulation from Launch to Impact", Convair-Astronautics Report ZN-7-305 dated 11 August 1958. Secret.
2. Battey "Performance Summary of the XSM-65-D Missile", Convair-Astronautics Report ZA-7-166, dated 30 October 1958. Secret.
3. Hill "Letter to R. H. Titman of Convair-Astronautics Flight Performance and Analysis Group", dated 19 June 1958. Secret.
4. MacMillan/Longobardo "Present Accuracy Capability of ARMA WS 107A Inertial Guidance System", ARMA Report DAG 1819E, dated August 1959. Secret.
5. "Evaluation of Radio Guidance System for C and D Series Missile Flights", G.E. Report SE-ER-66, dated 15 April 1960.

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.**SECRET**PAGE
REPORT
MODEL
DATE14
ZN-7-366

TABLE I

C.E.P. FOR RADIO-INERTIAL GUIDANCE SYSTEM

RANGE	TILT RATE	C.E.P.
NAUTICAL MILES	DEG/SEC	NAUTICAL MILES
4750	-0.10	0.34
4750	-0.05	0.43
4750	0.00	0.61
4750	+0.05	0.91
4750	+0.10	1.45
5500	-0.10	0.55
5500	-0.05	0.43
5500	0.00	0.44
5500	+0.05	0.64
5500	+0.10	1.10
6900	-0.10	1.11
6900	-0.05	1.09
6900	0.00	1.05
6900	-0.05	0.98
6900	+0.10	0.89
8700	-0.10	1.91
8700	-0.05	2.23
8700	0.00	2.63
8700	+0.05	3.08
8700	+0.10	3.89

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 15
REPORT ZN-7-366
MODEL
DATE

TABLE II

C.E.P. FOR ALL-INERTIAL GUIDANCE SYSTEM

RANGE NAUTICAL MILES	ATTITUDE DEGREES	C.E.P. NAUTICAL MILES
4750	31.1	1.03
4750	23.4	1.08
4750	15.8	1.19
5500	31.1	1.20
5500	23.4	1.25
5500	15.8	1.41
6900	31.1	1.51
6900	23.4	1.57
6900	15.8	1.83
6900	9.9	2.27
8700	31.1	1.91
8700	23.4	2.97
8700	15.8	2.37
8700	8.0	3.23

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA**SECRET**

TABLE III

PAGE 16
REPORT ZN-7-366
MODEL
DATETOTAL R.S.S. MISS FOR 1 σ ERRORS
IN RADIO-INERTIAL GUIDANCE SYSTEM

RANGE N. MILES	TILT RATE DEG/SEC	TARGET MISS	
		DOWNRANGE N. MILES	CROSSRANGE N. MILES
4750	-0.10	0.16	0.44
4750	-0.05	0.31	0.42
4750	0.00	0.64	0.41
4750	+0.05	1.17	0.40
4750	+0.10	2.03	0.40
5500	-0.10	0.46	0.47
5500	-0.05	0.29	0.45
5500	0.00	0.31	0.44
5500	+0.05	0.67	0.43
5500	+0.10	1.47	0.42
6900	-0.10	1.40	0.53
6900	-0.05	1.39	0.49
6900	0.00	1.35	0.47
6900	+0.05	1.23	0.46
6900	+0.10	1.09	0.45
8700	-0.10	2.60	0.74
8700	-0.05	3.11	0.65
8700	0.00	3.76	0.56
8700	+0.05	4.47	0.51
8700	+0.10	5.66	0.48

SECRET

CONVAIR - AERONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 17
REPORT ZN-7-366
MODEL
DATE

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 1 - RANGE OF 4750 NAUTICAL MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS					CROSSRANGE MISS PARTIALS				
	NAUT. MILES/UNIT ERROR					NAUT. MILES/UNIT ERROR				
	SUSTAINER TILT RATE, DEG/SEC					SUSTAINER TILT RATE, DEG/SEC				
	-0.10	-0.05	0.00	+0.05	+0.10	-0.10	-0.05	0.00	+0.05	+0.10
SLANT										
RANGE (R)	0.436	0.505	0.570	0.632	0.706	0.008	0.005	0.003	0.000	0.000
ELEVATION										
ANGLE (Y)	1.765	3.450	5.993	8.879	14.007	0.393	0.403	0.431	0.440	0.475
AZIMUTH										
ANGLE (A)	0.959	1.009	1.056	1.160	1.291	3.350	3.312	3.278	3.265	3.254
RANGE										
RATE (R)	0.713	0.783	0.855	0.980	1.150	0.000	0.001	0.001	0.001	0.001
LATERAL										
RATES (P)	69.31	72.95	84.71	85.25	97.37	266.9	255.9	246.1	239.7	234.7
(Q)	14.7	151.8	373.3	719.3	1287.	66.65	65.87	67.34	68.32	73.00

SECRET

CONVAIR -- ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 18
REPORT ZN-7-366
MODEL
DATE

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 1 - RANGE OF 4750 NAUTICAL MILES

PART B - TARGET MISSES

ERROR SOURCE	1 SIGMA ERRORS	DOWNRANGE TARGET MISSES					CROSSRANGE TARGET MISSES				
		NAUTICAL MILES					NAUTICAL MILES				
		SUST. TILT RATE, DEG/SEC					SUST. TILT RATE, DEG/SEC				
		- .10	- .05	0.00	+ .05	+ .10	- .10	- .05	0.00	+ .05	+ .10
SLANT											
RANGE (R)	0.020 KILOFEET	.01	.01	.01	.01	.01	.00	.00	.00	.00	.00
ELEVATION	-2										
ANGLE (Y)	4.37X10 M.RAD.	.08	.15	.26	.39	.61	.02	.02	.02	.02	.02
AZIMUTH	-2										
ANGLE (A)	4.37X10 M.RAD.	.04	.04	.05	.05	.06	.15	.15	.14	.14	.14
RANGE											
RATE (R)	0.1 FT/SEC	.07	.08	.09	.10	.12	.00	.00	.00	.00	.00
LATERAL											
RATES (P)	0.0015 FT/SEC	.10	.11	.13	.13	.15	.40	.38	.37	.36	.35
(Q)	0.0015 FT/SEC	.02	.23	.56	1.08	1.93	.10	.10	.10	.10	.11

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 19
REPORT ZN-7-366
MODEL
DATE

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 2 - RANGE OF 5500 NAUTICAL MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS					CROSSRANGE MISS PARTIALS				
	NAUT. MILES/UNIT ERROR					NAUT. MILES/UNIT ERROR				
	SUSTAINER TILT RATE, DEG/SEC					SUSTAINER TILT RATE, DEG/SEC				
	-0.10	-0.05	0.00	+0.05	+0.10	-0.10	-0.05	0.00	+0.05	+0.10
SLANT										
RANGE (R)	0.410	0.511	0.611	0.711	0.832	0.016	0.010	0.005	0.002	0.002
ELEVATION										
ANGLE (Y)	0.653	2.362	4.981	7.968	13.388	0.555	0.554	0.581	0.590	0.622
AZIMUTH										
ANGLE (A)	1.193	1.262	1.348	1.499	1.703	3.406	3.363	3.328	3.310	3.298
RANGE										
RATE (R)	0.809	0.903	1.009	1.179	1.410	0.000	0.001	0.001	0.001	0.002
LATERAL										
RATES (P)	86.0	90.1	106.7	108.6	125.0	277.9	265.9	258.1	250.9	244.3
(Q)	285.5	140.4	62.2	355.0	883.7	101.7	96.2	97.7	96.3	99.2

SECRET

CONVAIR — ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 20
REPORT ZN-7-366
MODEL
DATE

TABLE IV
SUMMARY OF RADIO INERTIAL ERROR STUDY
SECTION 2 - RANGE OF 5500 NAUTICAL MILES
PART B - TARGET MISSES

ERROR SOURCE	1 SIGMA ERRORS	DOWNRANGE TARGET MISSES					CROSSRANGE TARGET MISSES				
		NAUTICAL MILES					NAUTICAL MILES				
		SUST. TILT RATE, DEG/SEC					SUST. TILT RATE, DEG/SEC				
		-.10	-.05	0.00	+.05	+.10	-.10	-.05	0.00	+.05	+.10
SLANT RANGE (R)	0.020 KILOFEET	.01	.01	.01	.01	.02	.00	.00	.00	.00	.00
ELEVATION ANGLE (Ψ)	⁻² 4.37X10 M.RAD.	.03	.10	.22	.35	.59	.02	.02	.03	.03	.03
AZIMUTH ANGLE (A)	⁻² 4.37X10 M.RAD.	.05	.06	.06	.07	.07	.15	.15	.15	.15	.14
RANGE RATE (R)	[•] 0.1 FT/SEC	.08	.09	.10	.12	.14	.00	.00	.00	.00	.00
LATERAL RATE (P)	[•] 0.0015 FT/SEC	.13	.14	.16	.16	.19	.42	.40	.39	.38	.37
	[•] (Q) 0.0015 FT/SEC	.43	.21	.09	.53	1.33	.15	.14	.14	.14	.15

SECRET

SECRET

PAGE 21
REPORT ZN-7-366
MODEL
DATE

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 3 - RANGE OF 6900 NAUTICAL MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS					CROSSRANGE MISS PARTIALS				
	NAUT. MILES/UNIT ERROR					NAUT. MILES/UNIT ERROR				
	SUSTAINER TILT RATE , DEG/SEC					SUSTAINER TILT RATE , DEG/SEC				
	-0.10	-0.05	0.00	+0.05	+0.10	-0.10	-0.05	0.00	+0.05	+0.10
SLANT										
RANGE (R)	0.301	0.469	0.648	0.834	1.089	0.040	0.023	0.012	0.005	0.000
ELEVATION										
ANGLE (Y)	1.964	0.623	1.574	4.036	8.613	1.034	0.977	0.974	0.955	0.990
AZIMUTH										
ANGLE (A)	1.589	1.696	1.874	2.129	2.557	3.058	3.008	2.978	2.959	2.936
RANGE										
RATE (R)	0.948	1.096	1.271	1.530	1.918	0.000	0.001	0.002	0.003	0.003
LATERAL										
RATES (P)	113.9	120.0	145.2	148.7	179.4	263.1	252.6	247.4	237.1	231.8
(Q)	918.3	913.5	881.3	791.3	641.3	213.9	188.5	174.0	166.6	167.6

SECRET

CONFIDENTIAL

SECRET

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 3 - RANGE OF 6900 NAUTICAL MILES

PART B - TARGET MISSES

ERROR SOURCE	1 SIGMA ERRORS	DOWNRANGE TARGET MISSES					CROSSRANGE TARGET MISSES				
		NAUTICAL MILES					NAUTICAL MILES				
		SUST. TILT RATE, DEG/SEC					SUST. TILT RATE, DEG/SEC				
		-.10	-.05	0.00	+.05	+.10	-.10	-.05	0.00	+.05	+.10
SLANT											
RANGE (R)	0.020 KILOFEET	.01	.01	.01	.02	.02	.00	.00	.00	.00	.00
ELEVATION	-2										
ANGLE (W)	4.37X10 M.RAD.	.09	.03	.07	.18	.38	.05	.04	.04	.04	.04
AZIMUTH	-2										
ANGLE (A)	4.37X10 M.RAD.	.07	.07	.08	.09	.11	.13	.13	.13	.13	.13
RANGE	.										
RATE (R)	0.1 FT/SEC	.10	.11	.13	.15	.19	.00	.00	.00	.00	.00
LATERAL	.										
RATE (P)	0.0015 FT/SEC	.17	.18	.22	.22	.27	.40	.38	.37	.36	.35
(Q)	0.0015 FT/SEC	1.38	1.37	1.32	1.19	.96	.32	.28	.26	.25	.25

SECRET

SECRET

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 4 - RANGE OF 8700 NAUTICAL MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS					CROSSRANGE MISS PARTIALS				
	NAUT. MILES/UNIT ERROR					NAUT. MILES/UNIT ERROR				
	SUSTAINER TILT RATE • DEG/SEC					SUSTAINER TILT RATE • DEG/SEC				
	-0.10	-0.05	0.00	+0.05	+0.10	-0.10	-0.05	0.00	+0.05	+0.10
SLANT										
RANGE (R)	0.076	0.314	0.600	0.907	1.363	0.140	0.056	0.050	0.010	0.000
ELEVATION										
ANGLE (Y)	5.448	5.314	4.874	4.669	3.973	2.136	1.843	1.670	1.549	1.523
AZIMUTH										
ANGLE (A)	1.961	2.073	2.243	2.685	3.445	1.548	1.673	1.693	1.667	1.647
RANGE										
RATE (R)	1.001	1.203	1.466	1.835	2.410	0.006	0.004	0.004	0.005	0.005
LATERAL										
RATE (R)	148.3	145.9	163.7	180.7	229.3	159.4	164.7	167.3	156.8	152.3
(Q)	1715.	2061.	2497.	2936.	3770.	461.7	396.5	332.6	291.5	273.0

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

REPORT ZN-7-366
MODEL
DATE

TABLE IV

SUMMARY OF RADIO INERTIAL ERROR STUDY

SECTION 4 - RANGE OF 8700 NAUTICAL MILES

PART B - TARGET MISSES

ERROR SOURCE	1 σ SIGMA ERRORS	DOWNRANGE TARGET MISSES					CROSSRANGE TARGET MISSES				
		NAUTICAL MILES					NAUTICAL MILES				
		SUST. TILT RATE, DEG/SEC					SUST. TILT RATE, DEG/SEC				
		-0.10	-0.05	0.00	+0.05	+0.10	-0.10	-0.05	0.00	+0.05	+0.10
SLANT											
RANGE (R)	0.020 KILOFEET	.00	.00	.01	.02	.03	.00	.00	.00	.00	.00
ELEVATION	-2										
ANGLE (ψ)	4.37X10 M-RAD.	.24	.23	.21	.20	.17	.09	.08	.07	.07	.07
AZIMUTH	-2										
ANGLE (A)	4.37X10 M-RAD.	.09	.09	.10	.12	.15	.07	.07	.07	.07	.07
RANGE	.										
RATE (R)	0.1 FT/SEC	.10	.12	.15	.18	.24	.00	.00	.00	.00	.00
LATERAL	.										
RATE (P)	0.0015 FT/SEC	.22	.22	.25	.27	.34	.24	.25	.25	.24	.23
(Q)	0.0015 FT/SEC	2.57	3.09	3.75	4.45	5.66	.69	.60	.50	.44	.41

SECRET

SECRETREPORT ZN-7-366
MODEL
DATE

TABLE V

TOTAL R.S.S. MISS FOR 1σ ERRORS
IN ALL-INERTIAL GUIDANCE SYSTEM

RANGE N. MILES	ATTITUDE DEGREES	TARGET MISS	
		DOWNRANGE N. MILES	CROSSRANGE N. MILES
4750	31.1	1.03	0.73
4750	23.4	1.20	0.68
4750	15.8	1.45	0.63
5500	31.1	1.32	0.75
5500	23.4	1.48	0.70
5500	15.8	1.80	0.66
6900	31.1	1.90	0.73
6900	23.4	2.07	0.64
6900	15.8	2.52	0.60
6900	9.9	3.21	0.58
8700	31.1	2.72	0.45
8700	23.4	2.83	0.40
8700	15.8	3.43	0.39
8700	8.0	4.70	0.48

SECRET~~CONFIDENTIAL~~

SECRETREPORT
MODEL
DATE
ZN-7-366

TABLE VI

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 1 - RANGE OF 4750 N. MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS			CROSSRANGE MISS PARTIALS		
	NAUT. MILES/UNIT ERROR			NAUT. MILES/UNIT ERROR		
	SUSTAINER ATTITUDE , DEG.			SUSTAINER ATTITUDE , DEG.		
	31.1	23.4	15.8	31.1	23.4	15.8
GYRO=						
PITCH DRIFT						
A) CONSTANT	2.220	0.600	2.680	0.050	0.040	0.030
B) MASS UNBAL.	0.654	0.511	0.729	0.014	0.011	0.008
YAW DRIFT						
A) CONSTANT	0.770	1.010	1.050	2.990	3.070	3.030
B) MASS UNBAL.	1.200	1.500	1.517	1.789	1.972	2.350
ROLL DRIFT						
A) CONSTANT	0.470	0.500	0.420	1.890	1.520	1.130
B) MASS UNBAL						
BALL	0.778	0.844	0.639	SEE NOTE		
GIMBAL	0.778	0.844	0.639	3.200	2.578	1.856

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

SECRET

~~SECRET~~~~SECRET~~
PAGE 1
SERIAL ZN-7-366
MODEL
DATE

ACCELEROMETER=

ZERO

A) X-AXIS	218.0	288.3	303.7	2.3	3.3	1.7
B) Y-AXIS	10.3	15.0	17.0	49.0	51.3	45.7
C) Z-AXIS	114.7	148.7	176.3	0.7	1.0	0.0

SCALE FACTOR

A) X-AXIS	456.4	582.1	678.6	5.0	6.4	3.6
B) Z-AXIS	183.6	202.1	230.0	1.1	1.4	0.0

SECOND DEGREE

A) X AXIS	1437.5	1765.0	2262.5	15.0	20.0	17.5
B) Z AXIS	437.7	470.2	522.0	5.1	4.9	2.7

THIRD DEGREE

A) X AXIS	5178.0	6777.1	8532.0	156.2	178.0	66.8
B) Z AXIS	760.1	819.9	910.2	0.0	0.0	0.0

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	.0352	.0444	.0578	.0002	.0003	.0001
B) Y AXIS-ROLL	.0025	.0032	.0032	.0121	.0104	.0086
C) Y AXIS-YAW	.0033	.0047	.0059	.0160	.0164	.0161
D) X AXIS-PITCH	.0537	.0588	.0584	.0005	.0006	.0003

MISALIGNMENT

A) IN PITCH	.0185	.0138	.0007	.0004	.0003	.0003
B) IN YAW	.0044	.0054	.0063	.0162	.0164	.0162
C) IN ROLL	.0030	.0033	.0038	.0121	.0103	.0097

~~SECRET~~~~SECRET~~

SECRET

TABLE VI

REPORT 28
MODEL
DATE ZN-7-366

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 1 - RANGE OF 4750 N. MILES

PART B - TARGET MISSES

ERROR SOURCE	1σ ERROR	DOWNRANGE MISS			CROSSRANGE MISS		
		NAUTICAL MILES			NAUTICAL MILES		
		SUST. ATTITUDE, DEG.			SUST. ATTITUDE, DEG.		
		31.1	23.4	15.8	31.1	23.4	15.8

GYRO=

PITCH DRIFT

A) CONSTANT	.10 DEG/HR	0.22	0.06	0.27	0.00	0.00	0.00
B) MASS UNBAL.	.36 DEG/HR/G	0.24	0.18	0.26	0.00	0.00	0.00

YAW DRIFT

A) CONSTANT	.10 DEG/HR	0.08	0.10	0.11	0.30	0.31	0.30
B) MASS UNBAL.	.15 DEG/HR/G	0.10	0.23	0.23	0.27	0.30	0.35

ROLL DRIFT

A) CONSTANT	.10 DEG/HR	0.05	0.05	0.04	0.19	0.15	0.11
B) MASS UNBAL							

BALL	.15 DEG/HR/G	0.12	0.13	0.10	SEE NOTE		
GIMBAL	.15 DEG/HR/G	0.12	0.13	0.10	0.48	0.39	0.28

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

ACCELEROMETER=

ZERO

A) X AXIS	11×10^{-4} F/S	0.24	0.32	0.33	0.00	0.00	0.00
B) Y AXIS	6×10^{-4} F/S	0.01	0.01	0.01	0.03	0.03	0.03
C) Z AXIS	12×10^{-4} F/S	0.14	0.18	0.21	0.00	0.00	0.00

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 25
REPORT ZN-7-366
MODEL
DATE

SCALE FACTOR

A) X AXIS	⁻⁴ 7X10 ²	F/S/G	0.32	0.41	0.48	0.00	0.00	0.00
B) Z AXIS	⁻⁴ 7X10 ²	F/S/G	0.13	0.14	0.16	0.00	0.00	0.00

SECOND DEGREE

A) X AXIS	⁻⁴ 4X10 ^{2 2}	F/S/G	0.58	0.71	0.91	0.01	0.01	0.01
B) Z AXIS	⁻⁴ 4X10 ^{2 2}	F/S/G	0.18	0.19	0.21	0.00	0.00	0.00

THIRD DEGREE

A) X AXIS	⁻⁶ 45X10 ^{2 3}	F/S/G	0.23	0.31	0.38	0.01	0.01	0.00
B) Z AXIS	⁻⁶ 45X10 ^{2 3}	F/S/G	0.03	0.04	0.04	0.00	0.00	0.00

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	8 SEC.	0.28	0.36	0.46	0.00	0.00	0.00
B) Y AXIS-ROLL	10 SEC.	0.02	0.03	0.03	0.12	0.10	0.09
C) Y AXIS-YAW	10 SEC.	0.03	0.05	0.06	0.16	0.16	0.16
D) X AXIS-PITCH	8 SEC.	0.43	0.47	0.47	0.00	0.00	0.00

MISALIGNMENT

A) IN PITCH	6.1 SEC.	0.11	0.09	0.00	0.00	0.00	0.00
B) IN YAW	14.4 SEC.	0.06	0.08	0.09	0.23	0.24	0.23
C) IN ROLL	6.6 SEC.	0.02	0.02	0.02	0.08	0.07	0.06

TOTAL R.S.S. MISS=

ERROR SOURCE

DOWNRANGE MISS

CROSSRANGE MISS

NAUTICAL MILES

NAUTICAL MILES

SUSTAINER ATTITUDE, DEG.

SUSTAINER ATTITUDE, DEG.

	31.1	23.4	15.8	31.1	23.4	15.8
GYRO	0.42	0.37	0.47	0.65	0.60	0.55
ACCELEROMETER	0.78	0.97	1.19	0.03	0.04	0.03
PLATFORM	0.53	0.61	0.67	0.32	0.31	0.30

SECRET

SECRET

30
REPORT ZN-7-366
MODEL
DATE

TABLE VI

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 2 - RANGE OF 5500 N. MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS			CROSSRANGE MISS PARTIALS		
	NAUT. MILES/UNIT ERROR			NAUT. MILES/UNIT ERROR		
	SUSTAINER ATTITUDE , DEG.			SUSTAINER ATTITUDE , DEG.		
	31.1	23.4	15.8	31.1	23.4	15.8

GYRO=

PITCH DRIFT

A) CONSTANT	4.291	2.361	0.980	0.080	0.060	0.020
B) MASS UNBAL.	1.095	0.789	1.049	0.022	0.019	0.022

YAW DRIFT

A) CONSTANT	0.990	1.230	1.370	3.180	3.190	3.200
B) MASS UNBAL.	1.528	1.822	1.950	1.333	2.005	2.439

ROLL DRIFT

A) CONSTANT	0.572	0.590	0.540	2.010	1.558	1.159
B) MASS UNBAL						

BALL	0.956	1.006	0.839	SEE NOTE		
GIMBAL	0.956	1.006	0.839	3.478	2.706	1.967

NOTE* ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA**SECRET**PAGE 31
REPORT ZN-7-366
MODEL
DATE

ACCELEROMETER=

ZERO

A) X AXIS

B) Y AXIS

C) Z AXIS

277.7	344.3	384.3	5.0	6.7	6.3
11.3	17.0	21.7	51.0	50.7	45.3
122.0	150.0	184.7	2.0	2.7	2.3

SCALE FACTOR

A) X AXIS

B) Z AXIS

570.0	711.4	881.5	10.7	14.3	15.7
188.6	205.0	245.7	2.9	3.6	2.9

SECOND DEGREE

A) X AXIS

B) Z AXIS

1800.0	2205.0	2890.5	40.0	42.5	52.5
480.2	508.4	582.8	9.8	10.0	10.3

THIRD DEGREE

A) X AXIS

B) Z AXIS

7178	8910	11762	356.0	399.7	200.4
43	89	102	2.2	2.2	2.2

PLATFORM=

NONORTHOGCNAL

A) Z AXIS-PITCH

B) Y AXIS-ROLL

C) Y AXIS-YAW

D) X AXIS-PITCH

.0363	.0457	.0609	.0006	.0008	.0009
.0024	.0035	.0042	.0110	.0103	.0103
.0033	.0055	.0077	.0149	.0166	.0166
.0597	.0707	.0744	.0011	.0014	.0013

MISALIGNMENT

A) IN PITCH

B) IN YAW

C) IN ROLL

.0299	.0246	.0135	.0006	.0006	.0004
.0052	.0064	.0078	.0166	.0166	.0166
.0034	.0038	.0043	.0122	.0103	.0086

SECRET

FORM NO. E. T. 1 (4-57)

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

32
REPORT ZN-7-366
MODEL
DATE

TABLE VI

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 2 - RANGE OF 5500 N. MILES

PART B - TARGET MISSES

ERROR SOURCE	1σ ERROR	DOWNRANGE MISS			CROSSRANGE MISS		
		NAUTICAL MILES			NAUTICAL MILES		
		SUST. ATTITUDE, DEG.			SUST. ATTITUDE, DEG.		
		31.1	23.4	15.8	31.1	23.4	15.8

GYRO=

PITCH DRIFT

A) CONSTANT	.10 DEG/HR	0.43	0.24	0.10	0.01	0.01	0.00
B) MASS UNBAL.	.36 DEG/HR/G	0.39	0.28	0.38	0.01	0.01	0.01

YAW DRIFT

A) CONSTANT	.10 DEG/HR	0.10	0.12	0.14	0.32	0.32	0.32
B) MASS UNBAL.	.15 DEG/HR/G	0.23	0.27	0.29	0.20	0.30	0.37

ROLL DRIFT

A) CONSTANT	.10 DEG/HR	0.06	0.06	0.05	0.20	0.16	0.12
B) MASS UNBAL							

BALL	.15 DEG/HR/G	0.14	0.15	0.13	SEE NOTE		
GIMBAL	.15 DEG/HR/G	0.14	0.15	0.13	0.52	0.41	0.29

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

ACCELEROMETER=

ZERO

A) X AXIS	⁻⁴ ₂ 11X10 F/S	0.31	0.38	0.42	0.00	0.01	0.01
B) Y AXIS	⁻⁴ ₂ 6X10 F/S	0.01	0.01	0.01	0.03	0.03	0.03
C) Z AXIS	⁻⁴ ₂ 12X10 F/S	0.15	0.18	0.22	0.00	0.00	0.00

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA~~SECRET~~PAGE 33
REPORT 2N-7-366
MODEL
DATE

SCALE FACTOR

A) X AXIS	7X10 ⁻⁴	F/S/G	0.40	0.50	0.62	0.01	0.01	0.01
B) Z AXIS	7X10 ⁻⁴	F/S/G	0.13	0.14	0.17	0.00	0.00	0.00

SECOND DEGREE

A) X AXIS	4X10 ⁻⁴	F/S/G	0.72	0.88	1.16	0.02	0.02	0.02
B) Z AXIS	4X10 ⁻⁴	F/S/G	0.19	0.20	0.23	0.00	0.00	0.00

THIRD DEGREE

A) X AXIS	45X10 ⁻⁶	F/S/G	0.32	0.40	0.53	0.02	0.02	0.01
B) Z AXIS	45X10 ⁻⁶	F/S/G	0.00	0.00	0.00	0.00	0.00	0.00

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	8 SEC.	0.29	0.37	0.49	0.00	0.01	0.01
B) Y AXIS-ROLL	10 SEC.	0.02	0.04	0.04	0.11	0.10	0.10
C) Y AXIS-YAW	10 SEC.	0.03	0.05	0.08	0.15	0.17	0.17
D) X AXIS-PITCH	8 SEC.	0.48	0.57	0.60	0.01	0.01	0.01

MISALIGNMENT

A) IN PITCH	6.1 SEC.	0.18	0.15	0.08	0.00	0.00	0.00
B) IN YAW	14.4 SEC.	0.07	0.09	0.11	0.24	0.24	0.24
C) IN ROLL	6.6 SEC.	0.02	0.02	0.03	0.08	0.07	0.06

TOTAL R.S.S. MISS=

ERROR SOURCE

DOWNRANGE MISS

CROSSRANGE MISS

NAUTICAL MILES

NAUTICAL MILES

SUSTAINER ATTITUDE , DEG.

SUSTAINER ATTITUDE , DEG.

	31.1	23.4	15.8	31.1	23.4	15.8
GYRO	0.67	0.52	0.54	0.67	0.62	0.58
ACCELEROMETER	0.98	1.19	1.52	0.04	0.04	0.03
PLATFORM	0.60	0.70	0.79	0.31	0.32	0.31

~~SECRET~~

SECRET

TABLE VI

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 3 - RANGE OF 6900 N. MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS				CROSSRANGE MISS PARTIALS			
	NAUT. MILES/UNIT ERROR				NAUT. MILES/UNIT ERROR			
	SUSTAINER ATTITUDE , DEG.				SUSTAINER ATTITUDE , DEG.			
	31.1	23.4	15.8	9.9	31.1	23.4	15.8	9.9

GYRO=

PITCH DRIFT

A) CONSTANT	8.670	6.941	4.250	0.852	0.161	0.219	0.180	0.058
B) MASS UNBAL.	1.903	1.265	1.403	2.035	0.035	0.043	0.057	0.116

YAW DRIFT

A) CONSTANT	1.398	1.601	1.909	2.310	3.052	2.970	2.927	2.911
B) MASS UNBAL.	2.144	2.361	2.650	3.211	1.378	1.789	2.172	2.416

ROLL DRIFT

A) CONSTANT	0.511	0.710	0.782	0.738	1.916	1.441	1.042	0.761
B) MASS UNBAL								

BALL	0.956	1.250	1.261	0.989	SEE NOTE			
GIMBAL	0.956	1.250	1.261	0.989	3.444	2.578	1.822	1.278

NOTE: ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

SECRET

SECRET

ACCELEROMETER=

ZERO

A) X AXIS	347.0	440.7	553.3	724.7	7.3	14.3	21.7	31.3
B) Y AXIS	8.0	20.3	35.0	53.3	44.0	42.7	39.7	38.0
C) Z AXIS	110.0	135.7	177.0	232.3	2.7	4.3	6.7	9.7

SCALE FACTOR

A) X AXIS	743.6	945.7	1247.8	1652.1	15.7	30.7	49.3	72.1
B) Z AXIS	175.0	194.3	224.3	275.0	4.3	6.4	8.6	11.4

SECOND DEGREE

A) X AXIS	2295	3078	4104	5438	85.0	97.5	140.0	185.0
B) Z AXIS	480	533	633	780	17.4	17.6	19.6	24.8

THIRD DEGREE

A) X AXIS	10692	12958	18558	23692	578.1	600.2	710.7	822.0
B) Z AXIS	93	96	109	132	2.2	3.2	4.1	4.7

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	.0333	.0414	.0557	.0750	.0008	.0013	.0021	.0031
B) Y AXIS-ROLL	.0019	.0042	.0064	.0086	.0108	.0087	.0071	.0058
C) Y AXIS-YAW	.0027	.0068	.0122	.0189	.0151	.0147	.0144	.0141
D) X AXIS-PITCH	.0851	.0920	.1019	.1165	.0018	.0030	.0040	.0051

MISALIGNMENT

A) IN PITCH	.0521	.0502	.0458	.0411	.0010	.0016	.0018	.0019
B) IN YAW	.0064	.0080	.0103	.0137	.0151	.0146	.0145	.0143
C) IN ROLL	.0027	.0045	.0060	.0075	.0108	.0087	.0071	.0059

SECRET

SECRET

TABLE VI

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 3 - RANGE OF 6900 N. MILES

PART B - TARGET MISSES

ERROR SOURCE	16 ERROR	DOWNRANGE MISS				CROSSRANGE MISS			
		NAUTICAL MILES				NAUTICAL MILES			
		SUST. ATTITUDE, DEG.				SUST. ATTITUDE, DEG.			
		31.1	23.4	15.8	9.9	31.1	23.4	15.8	9.9

GYRO=

PITCH DRIFT

A) CONSTANT	.10 DEG/HR	0.87	0.69	0.43	0.09	0.02	0.02	0.02	0.01
B) MASS UNBAL	.36 DEG/HR/G	0.69	0.46	0.51	0.73	0.01	0.02	0.02	0.04

YAW DRIFT

A) CONSTANT	.10 DEG/HR	0.14	0.16	0.19	0.23	0.31	0.30	0.29	0.29
B) MASS UNBAL	.15 DEG/HR/G	0.32	0.35	0.40	0.48	0.21	0.27	0.33	0.36

ROLL DRIFT

A) CONSTANT	.10 DEG/HR	0.05	0.07	0.08	0.07	0.19	0.14	0.10	0.08
B) MASS UNBAL									

BALL	.15 DEG/HR/G	0.14	0.19	0.19	0.15	SEE NOTE			
GIMBAL	.15 DEG/HR/G	0.14	0.19	0.19	0.15	0.52	0.39	0.27	0.19

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

ACCELEROMETER=

ZERO

A) X AXIS	11X10 ⁻⁴ F/S	0.38	0.48	0.61	0.80	0.01	0.02	0.02	0.03
B) Y AXIS	6X10 ⁻⁴ F/S	0.00	0.01	0.02	0.03	0.03	0.03	0.02	0.02
C) Z AXIS	12X10 ⁻⁴ F/S	0.13	0.16	0.21	0.28	0.00	0.00	0.01	0.01

SECRET

CONVAM - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS
SAN DIEGO, CALIFORNIA

SECRET

REPORT
MODEL
DATE

37
ZN-7-366

SCALE FACTOR

A) X AXIS	7X10 ⁻⁴ F/S/G	0.52	0.66	0.87	1.16	0.01	0.02	0.03	0.05
B) Z AXIS	7X10 ⁻⁴ F/S/G	0.12	0.14	0.16	0.19	0.00	0.00	0.01	0.01

SECOND DEGREE

A) X AXIS	4X10 ⁻⁴ F/S/G	0.92	1.23	1.64	2.18	0.03	0.04	0.06	0.07
B) Z AXIS	4X10 ⁻⁴ F/S/G	0.19	0.21	0.25	0.31	0.01	0.01	0.01	0.01

THIRD DEGREE

A) X AXIS	45X10 ⁻⁶ F/S/G	0.48	0.58	0.84	1.07	0.03	0.03	0.03	0.04
B) Z AXIS	45X10 ⁻⁶ F/S/G	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	8 SEC.	0.27	0.33	0.45	0.60	0.01	0.01	0.02	0.03
B) Y AXIS-ROLL	10 SEC.	0.02	0.04	0.06	0.09	0.11	0.09	0.07	0.06
C) Y AXIS-YAW	10 SEC.	0.03	0.07	0.12	0.19	0.15	0.15	0.14	0.14
D) X AXIS-PITCH	8 SEC.	0.68	0.74	0.82	0.93	0.01	0.02	0.03	0.04

MISALIGNMENT

A) IN PITCH	6.1 SEC.	0.32	0.30	0.28	0.25	0.01	0.01	0.01	0.01
B) IN YAW	14.4 SEC.	0.09	0.11	0.15	0.20	0.22	0.21	0.21	0.21
C) IN ROLL	6.6 SEC.	0.02	0.03	0.04	0.05	0.07	0.06	0.05	0.04

TOTAL R.S.S. MISS=

ERROR SOURCE

DOWNRANGE MISS

CROSSRANGE MISS

NAUTICAL MILES

NAUTICAL MILES

SUSTAINER ATTITUDE , DEG.

SUSTAINER ATTITUDE , DEG.

	31.1	23.4	15.8	9.9	31.1	23.4	15.8	9.9
GYRO	1.18	0.96	0.84	0.94	0.66	0.58	0.53	0.51
ACCELEROMETER	1.25	1.62	2.16	2.84	0.05	0.06	0.08	0.11
PLATFORM	0.80	0.88	0.99	1.17	0.30	0.28	0.27	0.26

SECRET

~~CONFIDENTIAL~~

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

PAGE 38
REPORT ZN-7-366
MODEL
DATE

SECRET
TABLE VI

~~CONFIDENTIAL~~

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 4 - RANGE OF 8700 N. MILES

PART A - MISS PARTIALS

ERROR SOURCE	DOWNRANGE MISS PARTIALS				CROSSRANGE MISS PARTIALS			
	NAUT. MILES/UNIT ERROR				NAUT. MILES/UNIT ERROR			
	SUSTAINER ATTITUDE , DEG.				SUSTAINER ATTITUDE , DEG.			
	31.1	23.4	15.8	8.0	31.1	23.4	15.8	8.0

GYRO=

PITCH DRIFT

A) CONSTANT	15.39	14.10	12.81	10.54	0.109	0.531	1.138	1.320
B) MASS UNBAL.	2.988	1.592	1.208	2.646	0.019	0.059	0.108	0.327

YAW DRIFT

A) CONSTANT	1.702	1.820	1.890	2.101	1.901	1.788	1.671	1.550
B) MASS UNBAL.	2.622	2.683	2.878	3.489	0.784	1.007	1.272	1.448

ROLL DRIFT

A) CONSTANT	0.071	0.731	1.470	1.902	1.179	0.848	0.491	0.161
B) MASS UNBAL								

BALL	0.159	1.318	2.571	2.830	SEE NOTE			
GIMBAL	0.159	1.318	2.571	2.830	2.244	1.617	0.922	0.322

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

SECRET

~~CONFIDENTIAL~~

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA**SECRET**PAGE 39
REPORT ZN-7-366
MODEL
DATE~~CONFIDENTIAL~~

ACCELEROMETER=

ZERO

A) X AXIS	395.3	515.0	670.7	1009.7	2.0	20.0	59.7	125.3
B) Y AXIS	4.7	20.3	66.0	14.1	22.0	21.7	15.7	3.7
C) Z AXIS	66.3	83.3	108.3	169.7	0.0	3.3	9.3	20.7

SCALE FACTOR

A) X AXIS	902.9	1155.7	1562.9	2357.9	4.3	45.0	139.3	292.9
B) Z AXIS	106.4	122.1	149.3	220.7	0.0	5.0	12.9	27.1

SECOND DEGREE

A) X AXIS	3255	4030	5438	7950	120.0	155.0	220.0	262.5
B) Z AXIS	355	460	605	758	15.0	17.5	22.5	25.0

THIRD DEGREE

A) X AXIS	15510	18490	25778	36004	578.0	71.0	1022.1	1489.2
B) Z AXIS	620	800	980	1160	2.2	3.2	4.1	4.7

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	.0186	.0238	.0319	.0495	.0001	.0010	.0030	.0028
B) Y AXIS-ROLL	.0012	.0043	.0122	.0215	.0057	.0045	.0026	.0017
C) Y AXIS-YAW	.0017	.0070	.0239	.0514	.0084	.0082	.0063	.0020
D) X AXIS-PITCH	.1012	.1098	.1241	.1534	.0005	.0042	.0110	.0190

MISALIGNMENT

A) IN PITCH	.0827	.0857	.0914	.1047	.0006	.0032	.0081	.0130
B) IN YAW	.0063	.0087	.0123	.0190	.0085	.0081	.0073	.0060
C) IN ROLL	.0004	.0044	.0111	.0184	.0057	.0045	.0027	.0006

SECRET~~CONFIDENTIAL~~

SECRET

TABLE VI

PAGE 40
REPORT ZN-7-366
MODEL
DATE

SUMMARY OF ALL INERTIAL ERROR STUDY

SECTION 4 - RANGE OF 8700 N. MILES

PART B - TARGET MISSES

ERROR SOURCE	1σ ERROR	DOWNRANGE MISS				CROSSRANGE MISS			
		NAUTICAL MILES				NAUTICAL MILES			
		SUST. ATTITUDE, DEG.				SUST. ATTITUDE, DEG.			
		31.1	23.4	15.8	8.0	31.1	23.4	15.8	8.0

GYRO=

PITCH DRIFT

A) CONSTANT	.10 DEG/HR	1.54	1.41	1.28	1.05	0.01	0.05	0.11	0.15
B) MASS UNBAL	.36 DEG/HR/G	1.04	0.57	0.44	0.95	0.01	0.02	0.04	0.12

YAW DRIFT

A) CONSTANT	.10 DEG/HR	0.17	0.18	0.19	0.21	0.19	0.18	0.17	0.16
B) MASS UNBAL	.15 DEG/HR	0.39	0.40	0.43	0.52	0.12	0.15	0.19	0.22

ROLL DRIFT

A) CONSTANT	.10 DEG/HR	0.01	0.07	0.15	0.19	0.12	0.09	0.05	0.02
B) MASS UNBAL									

BALL	.15 DEG/HR/G	0.02	0.20	0.39	0.42	SEE NOTE			
------	--------------	------	------	------	------	----------	--	--	--

GIMBAL	.15 DEG/HR/G	0.02	0.20	0.39	0.42	0.34	0.24	0.14	0.05
--------	--------------	------	------	------	------	------	------	------	------

NOTE= ROLL AND YAW CROSSRANGE ERRORS DUE TO MASS UNBALANCE ALONG SPIN AXIS OF BALL CANCEL AND HAVE BEEN COMBINED IN THE YAW DRIFT PORTION OF THESE TABLES.

ACCELEROMETER=

ZERO

A) X AXIS	⁻⁴ 2 11X10 F/S	0.44	0.57	0.74	1.11	0.00	0.02	0.07	0.14
B) Y AXIS	⁻⁴ 2 6X10 F/S	0.00	0.01	0.04	0.01	0.01	0.01	0.01	0.00
C) Z AXIS	⁻⁴ 2 12X10 F/S	0.08	0.10	0.13	0.20	0.00	0.00	0.01	0.02

SECRET

CONVAIR - ASTRONAUTICS
DIVISION OF GENERAL DYNAMICS CORP.
SAN DIEGO, CALIFORNIA

SECRET

PAGE 1/1
~~CONFIDENTIAL~~
DATE

SCALE FACTOR

A) X AXIS	$7 \times 10^{-4} \frac{F/S/G}{2}$	0.63	0.81	1.09	1.65	0.00	0.03	0.10	0.20
B) Z AXIS	$7 \times 10^{-4} \frac{F/S/G}{2}$	0.07	0.09	0.10	0.15	0.00	0.00	0.01	0.02

SECOND DEGREE

A) X AXIS	$4 \times 10^{-4} \frac{F/S/G}{2^2}$	1.30	1.61	2.18	3.18	0.05	0.06	0.09	0.11
B) Z AXIS	$4 \times 10^{-4} \frac{F/S/G}{2^2}$	0.14	0.18	0.24	0.30	0.01	0.01	0.01	0.01

THIRD DEGREE

A) X AXIS	$45 \times 10^{-6} \frac{F/S/G}{2^3}$	0.70	0.83	1.16	1.62	0.03	0.03	0.05	0.07
B) Z AXIS	$45 \times 10^{-6} \frac{F/S/G}{2^3}$	0.03	0.04	0.04	0.05	0.00	0.00	0.00	0.00

PLATFORM=

NONORTHOGONAL

A) Z AXIS-PITCH	8 SEC.	0.15	0.19	0.26	0.40	0.00	0.01	0.02	0.02
B) Y AXIS-ROLL	10 SEC.	0.01	0.04	0.12	0.22	0.06	0.05	0.03	0.02
C) Y AXIS-YAW	10 SEC.	0.02	0.07	0.24	0.51	0.08	0.08	0.06	0.02
D) X AXIS-PITCH	8 SEC.	0.81	0.88	0.99	1.23	0.00	0.03	0.09	0.15

MISALIGNMENT

A) IN PITCH	6.1 SEC.	0.50	0.52	0.56	0.64	0.00	0.02	0.05	0.08
B) IN YAW	14.4 SEC.	0.09	0.13	0.18	0.27	0.12	0.12	0.11	0.09
C) IN ROLL	6.6 SEC.	0.00	0.03	0.07	0.12	0.04	0.03	0.02	0.00

TOTAL R.S.S. MISS=

ERROR SOURCE

DOWNRANGE MISS

CROSSRANGE MISS

NAUTICAL MILES

NAUTICAL MILES

GYRO

ACCELEROMETER

PLATFORM

SUSTAINER ATTITUDE , DEG.


SUSTAINER ATTITUDE , DEG.

31.1	23.4	15.8	8.0	31.1	23.4	15.8	8.0
1.91	1.61	1.54	1.65	0.42	0.35	0.32	0.32
1.67	2.08	2.81	4.11	0.05	0.08	0.16	0.29
0.97	1.05	1.21	1.57	0.16	0.16	0.16	0.20

SECRET

SECRET


ZN-7-366
Page 42



SECRET

SECRET

7-366 171
Page




SECRET

~~SECRET~~

7N-7-366

FIGURE 2(G)


PAYLOAD VS. RANGE FOR VARIOUS INERTIAL ATTITUDES



~~SECRET~~

SECRET

Page 4547




SECRET

SECRET

ZN-7-366
Page 46

FIGURE 3


C. I. P. FOR RIG SYSTEM



SECRET

SECRET


2N-7-366
Page 47



SECRET

SECRET

ZN-7-366
Page 48




SECRET

~~SECRET~~

8NL7-366
Page 49


FIGURE 5
TOTAL CROSSRANGE MISS FOR RIG SYSTEM



K-2 10X10 TO THE CM. 389T-140
KUPPEL & EBBEN CO. NEW YORK, N.Y.
ALBANY, N.Y.

~~SECRET~~

Page 50



SECRET


K+W
10 X 10 TO THE CM.
SUPPLY & ORDER CO.
ALBANY, N.Y.
359T-14G
MAY 11 1964

SECRET

ZN-7-366
Page 51

FIGURE 7(b)

DOWNRANGE MILES DUE TO MAJOR RIG ERROR SOURCES
FOR RANGE OF 5500 N. MILES




Gy - Sustainer Stage Roll Rate, deg/sec.

SECRET

REF ID: A68000
10X10 TO THE CM 3897.14G
REPRODUCED BY THE CM 3897.14G
REPRODUCED BY THE CM 3897.14G

SECRET


2N-7-366
Page 52



SECRET

SECRET


ZN-7-500
Page 53



SECRET

SECRET


~~CONFIDENTIAL~~ 2N-7-366
Page 54



SECRET

SECRET

Page 55



SECRET


SECRET

Page 56

FIGURE 8(c)

CROSSRANGE MISS DUE TO MAJOR RIG ERROR SOURCES
FOR RANGE OF 6900 N. MILES

Crossrange Miss, N. miles




ω_r - Sustainer Stage Tilt Rate, deg/sec.

SECRET

SECRET


ZN-7-366
Page 57



SECRET

SECRET

2N-7-306
Page 58




SECRET

~~SECRET~~

ZN-7-366
Page 59

FIGURE 10

TOTAL AIG SYSTEM CROSSRANGE MISS




* Sustainer Stage Inertial Attitude, deg.

~~SECRET~~

~~SECRET~~

44-7-366
Page 60

FIGURE 11(a)
DORMANCE MISS DUE TO MAJOR AIR ERROR SOURCES
FOR RANGE OF 4750 N. MILES



~~SECRET~~


~~SECRET~~

Page 61

FIGURE 11(b)

DOORANCE MISS DUE TO MAJOR AIG ERROR SOURCES

FOR RANGE OF 1000 N. MILES



K-E 10 X 11 TO THE CM. 380T-14
KEUFFEL & ESSER CO.
ALBANY, N. Y.


~~SECRET~~

SECRET

Page 62

FIGURE 11(e)

DOWN-RANGE MISS DUE TO MAJOR AID ERROR SOURCES
FOR RANGE OF 6900 N. MILES



KEUFFEL & ESSER CO. ALBANY, N.Y.


SECRET

SECRET

24-7-306
Page 63

FIGURE 11(d)

DOWNRANGE MISS DUE TO NAJCE AIG ERROR SOURCES
FOR RANGE OF 8700 N. MILES



REUFFEL & EBER CO. BOSTON 14
ALBANY 2


SECRET

SECRET

ZN-7-366
Page 62

FIGURE 12(a)

CROSSRANGE MISS DUE TO MAJOR AIO ERROR SOURCES
FOR RANGE OF 2250 N. MILES




SECRET

SECRET

21-2-166
Page 65

FIGURE 12(6)

CROSS-RANGE MISS DUE TO MAJOR AIG ERROR SOURCES
FOR RANGE OF 3500 N. MILES




11/2 KEMPTEL & KEMP CO. BOSTON 11
ALBANY 9

SECRET

SECRET

Page 66

FIGURE 12(a)
CROSSRANGE MISS DUE TO MATCH AND ERROR SOURCES
FOR RANGE OF 1900 N. MILES




13-48 KLUFFEL & ESEER CO. BOSTON 14
ALBANY 8

SECRET

SECRET

Page 67


FIGURE 12(d)
CROSSRANGE MISS DUE TO MAJOR IIG ERROR SOURCES
FOR RANGE OF 3700 N. MILES



SECRET

SECRET


ZN-7-366
Page 68



SECRET

SECRET

20-7-566
Page 69




SECRET

SECRET

7-7-36
Page 10

FIGURE 14 UNCLASSIFIED
CIRCULAR ERROR PROBABILITY
FROM
ELLIPTICAL PROBABILITY DISTRIBUTION

L = Larger of R.S.S. Longrange and Crossrange Miss
S = Smaller of R.S.S. Downrange and Crossrange Miss




UNCLASSIFIED

18/10/19/11/11

ALANINE

SECRET



~~SECRET~~